

Jackleg Drills Model 260B



JACKLEG DRILL FEATURES

- High penetration rate
- High torque
- Convenient operating controls
- Push button air leg retraction
- Automatic water pressure regulation
- Air operated stainless steel water valve
- Positive lubrication and front-end blow
- Parts interchangeability with CANUN 260B Stoper, Sinker & Quarry Drills

OPTIONS

Exhaust	Standard	Integral steel muffler	
Airleg travel	1270mm/50"	991mm/39"	762mm/30"
Airleg	Standard	Corrosion-resistant	
Lubricator	CANUN UN125		
Water shutoff valve	CANUN 95101		
Shop repair tools			
Sinker handle assembly			
Telescoping airleg adapter assembly			

SPECIFICATIONS	US / IMP	METRIC
Cylinder diameter	3.125"	79.4mm
Piston stroke	2.875"	73.25mm
Piston working stroke	2.625"	66.7mm
Impact frequency	2250.0bpm	2250.0bpm
Drill length	27.0"	686.0mm
Weight of drill	72.75lbs	33.0kg
Weight of airleg	33.00lbs	15.0kg
Airleg travel	50.00"	1270.0mm
Air bore diameter	2.625"	67.0mm
Air consumption (90 psi)	170.0 cfm	4.9 cubic meters
Steel size (standard)	7/8" x 4 1/4"	22mm x 108mm