

SOFT ANCHORAGE CONNECTORS



Anchor slings

- Pass-through D-ring
- Rated 5,000 lbs. (22.2 kN)
- Made of polyester webbing
- Heavy duty back pad

V4136

- 15-in. (0.4 m) length

V4135 (shown)

- 3-ft. (0.9 m) length

V4165

- 6-ft. (1.8 m) length



Sling choker

- Rated 5,000 lbs. (22.2 kN)
- Made of polyester webbing

V4115

- 15-in. (0.4 m) length


Anchorage connector

The purpose of the shock absorber is to lower the impact forces caused by the fall.

- Made of a 1¼-in. (45 mm) lightweight continuous web
- Shock absorber covered with a tubular sleeve
- 2¼-in. (57 mm) snap hook
- D-ring connector

V41PRE

- Anchorage connector



V4172



V41906

Wire rope slings

- 6 ft. x ¼ in. (1.8 m x 6 mm)
- Vinyl covered

V4172

- Wire rope sling

V41906

- ¾-in. (19 mm) self-locking snap hook
- O-ring



Anchor straps

- Rated 5,000 lbs. (22.2 kN)
- Made of nylon webbing
- 3½ ft. (1.1 m)

V41803

- For structural member
- With loop

V41813 (shown)

- For structural member
- D-ring

V41823

- For rebar steel
- Protective sleeve
- Loop

V41833

- For rebar steel
- Protective sleeve
- D-ring



Endless slings

V41321

- 18-in. (0.5 m) endless sling

V41323 (shown)

- 3-ft. (0.9 m) endless sling

V41326

- 6-ft. (1.8 m) endless sling